



EDGECHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

PRODUCT DATA SHEET

Rev. 2

T.D.S.

EDGECHEM RED OXIDE PRIMER

DESCRIPTION

A top quality general purpose Alkyd primer designed to give protection against corrosion to all iron and steel surfaces exposed to the elements.

PERFORMANCE FEATURES

- Fast drying
- Good metal protection
- Exceptional storage stability

PHYSICAL PROPERTIES

Colour	:	Red Iron Oxide
Specific Gravity	:	1.30
Flash Point	:	40°C (112°F) based on major solvent component
Gloss	:	Slight
Drying Time		
To Touch	:	15-30 minutes
Hard Dry	:	24 hours
To Recoat	:	overnight

COVERAGE RATE

380 – 400 square feet per gallon.

SUGGESTED USES

Brush or spray on iron and steel surfaces for corrosion resistance.

RED OXIDE PRIMER**SURFACE PREPARATION**

Remove all oil, grease, rust, dust and other loose material. Apply the first coat of Primer immediately after cleaning.

APPLICATION

Brush on substrate – no reduction necessary

Spray – reduce with up to 500 ml Edgechem Oil Paint Reducer to 3.75 ltr Primer. Apply even coats.

SHELFLIFE

2 years

CLEAN UP

Clean up with Edgechem Oil Paint Reducer.